



Applications

Our 'Drain Master' Sets are used for cleaning, clearing and unblocking drainpipes.

Manufactured in the UK from polypropylene and are joined by brass ferrules, which are riveted to the polypropylene for maximum security.

Supplied with either a Universal or Lockfast Brass Couplings, and a range of tools and fittings to suit your needs. The Universal type of coupling has a coarse thread and simply screws together – rod rotation must always be in a clockwise direction to avoid parting. The Lockfast coupling has a finer thread – joining is effected by locating the square pin on the male joint in the slot on the female joint. The loose nut is then tightened to complete the joint. The rod can now be safely rotated in either direction.


Features

- ~ Universal or Lockfast fittings available
- ~ Each set supplied with 10 Polypropylene Rods 3/4" Dia x 3ft with Riveted Brass Ferrules
- ~ C/W Plunger and Double Worm as standard; drop scraper available with 363800 [Other tools available in our range]
- ~ Rods strapped together and polybagged
- ~ Supplied in canvas bag



Dimensional Data

915mm



Technical Data

Dimension	3/4" Dia x 3ft
Product Codes	363786 [Canvas Bag Universal Fitting c/w Plunger & Double Worm] 363787 [Canvas Bag - Lockfast Fitting c/w Plunger & Double Worm]